



Performance Guide

Solar Heat Rejection Glare Reduction UV Reduction Fade Reduction Safety & Security One-Way Privacy Two-Way Privacy Scratch Coating Warranty Period ★★★☆☆
★★★☆☆
★★★☆☆
★★★☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆☆
10 Years

Key: Excellent-★★★★★ Some Benefit- ★☆☆☆☆ N/A- ☆☆☆☆☆

Performance Data

Total Solar Energy Rejected	68%
Solar Energy Reflected	29%
Solar Energy Absorbed	58%
Solar Energy Transmitted	14%
Visible Light Transmitted	21%
Visible Light Reflected- Interior	31%
Visible Light Reflected- Exterior	32%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.30
Solar Heat Gain Coeff. (g Value)	0.32
Emissivity	0.76
Glare Reduction	78%

Physical Properties

Description	Dark Grey
Material	PET
Liner	Coated PET
Film Thickness	50u
Structure	Dual Ply
Adhesive Type	Acrylic
Adhesive Type	ACTYIIC

Notes

All data is based on film applied to 3mm clear float glass. Performance results are subject to varation within industry standards and are only intended for estimating purposes. There may be restrictions concerning the suitability of this product to certain glazing types. It is the users responsibility to ensure the product is suitable for the intended use. For more details please contact us.

Installation

Should be undertaken by professional window film installers. As per manufacturers instructions, film can only be applied in tempurture of +5C. For best results, a clean and dust free area environment should be provided.

Drying

The curing period of the adhesive to the window often causes a slightly misty appearance. This is normal and will clear in a short period of time (usually around 7 - 20 days) depending on the thickness of the film.

In very cold weather the curing process may take longer and the mistiness more pronounced. Nevertheless the film will clear to provide perfect clarity. Film can take up to 14 days to cure/dry.



Description

A Dark Neutral or tinted film adds a subtle grey or steel appearance to glazing. Extremely effective reduction in heat gain and glare that preserves the natural view through the glass. This range of tinting window film provides a natural grey appearance, inside and out.

This product carries a full 10 years manufacturer's warranty when professionally installed

Neutral Films Provide

- 1- Neutral colour-provides natural grey appearance
- 2- Used on heritage buildings and in conservation areas
- 3- Upgraded building appearance
- 4- More comfortable internal environment
- 5- Daytime Privacy
- 6-99+% UV Block

For examples of all our window films or for more information of our services including manifestations and printed graphics, please visit our website

www.windowfilms2000.co.uk





T- 0844 870 7571 **E-** info@windowfilms2000.co.uk