

Silver 20 Heat & Glare Control Window Film

## **Performance Guide**

 $\star \star \star \star \star$ Solar Heat Rejection  $\star \star \star \star \star$ Glare Reduction **UV** Reduction  $\star \star \star \star \star$ Fade Reduction  $\star \star \star \star \star \star$ Safety & Security  $\triangle \triangle \triangle \triangle \triangle$ One-Way Privacy  $\star \star \star \star \star \dot{}$ Two-Way Privacy ☆ ☆ ☆ ☆ ☆ Scratch Coating Yes Warranty Period 10 Years



#### **Performance Data**

Total Solar Energy Rejected	80%
Solar Energy Reflected	55%
Solar Energy Absorbed	33%
Solar Energy Transmitted	12%
Visible Light Transmitted	18%
Visible Light Reflected- Interior	58%
Visible Light Reflected- Exterior	60%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.25
Solar Heat Gain Coeff. (g Value)	0.22
Emissivity	0.72
Glare Reduction	83%

# **Physical Properties**

Description	Dark Silver
Material	PET
Liner	Coated PET
Film Thickness	50u
Structure	Single Ply
Adhesive Type	Acrylic

#### **Notes**

All data is based on film applied to 3mm clear float glass. Performance results are subject to varation within industry standards and are only intended for estimating purposes. There may be restrictions concerning the suitabliity of this product to certain glazing types. It is the users responsibility to ensure the product is suitable for the intended use. For more details please contact us.

## Installation

Should be undertaken by professional window film installers. As per manufacturers instructions, film can only be applied in tempurture of +5C. For best results, a clean and dust free area environment should be provided.

### **Drying**

The curing period of the adhesive to the window often causes a slightly misty appearance. This is normal and will clear in a short period of time (usually around 7 - 20 days) depending on the thickness of the film.

In very cold weather the curing process may take longer and the mistiness more ronounced. Nevertheless the film will clear to provide perfect clarity. Film can take up to 14 days to cure/dry.



# **Description**

Dark Silver Reflective, high performing and most widely used solar film. Offers daytime privacy, screening out unsightly areas. Gives an external mirrored appearance to glazing. Reduces high levels of incoming solar heat and glare.

This product carries a full 10 years manufacturer's warranty when professionally installed

# **Reflective Films Provide**

- 1- Excellant solar heat and glare reduction
- 2- Highest levels of energy efficiency
- 3- Upgraded building appearance
- 4- More comfortable internal environment
- 5- Daytime Privacy
- 6-99+% UV Block

For examples of all our window films or for more information of our services including manifestations and printed graphics, please visit our website

www.windowfilms2000.co.uk





